



STK 90°Angle Head Screwdriver


SHIUTEK Auto Shut Off-Lever Start




Square Driver 1/4"



Square Driver 3/8"



Hex-Driver 1/4"



Bit

8KA2 1/4" SQ

8KA3 3/8" SQ

8KAH Hex 6.35mm (1/4")

- Design for comfortable grip
- Unique quickly auto shut-off air, cushion clutch design
- Use (# 1PH) Philips cross screwdriver from external easily to adjust torque
- Highly trustworthiness design
- Parts designed for lower worn out and longer lifetime
- Variety rpm speed for flexibility choices
- The locking system is suitable for industrial use

Model	Spec Drive	Torque Range	Free Speed	Air Consumption	Distance Center to Side	Noise	Air Inlet Thread	Net Weight	Overall Length
STK	in	N-M max.(ft-lbs)	RPM	L/min	mm	dba	PT	g	mm
8KA2-2	1/4"	1.9~ 6.4 (1.4~ 4.7)	760	440	13	72	1/4"	870	300
8KA2-3		1.9~ 8.2 (1.4~ 6.0)	550						
8KA2-4		1.9~ 9.0 (1.4~ 6.6)	440						
8KA2-5		1.9~ 10.0 (1.4~ 7.4)	320						
8KA3-2	3/8"	1.9~ 6.4 (1.4~ 4.7)	760	440	13	72	1/4"	870	300
8KA3-3		1.9~ 8.2 (1.4~ 6.0)	550						
8KA3-4		1.9~ 9.0 (1.4~ 6.6)	440						
8KA3-5		1.9~ 10.0 (1.4~ 7.4)	320						
8KAH-2	Female hex 6.35	1.9~ 6.4 (1.4~ 4.7)	760	440	13	72	1/4"	870	300
8KAH-3		1.9~ 8.2 (1.4~ 6.0)	550						
8KAH-4		1.9~ 9.0 (1.4~ 6.6)	440						
8KAH-5		1.9~ 10.0 (1.4~ 7.4)	320						